

Accuracy Evaluation of the Landsat 7 ACCA Algorithm

Richard Irish
Landsat Project Science Office
Goddard Space Flight Center



ACCA Implementation

Operational Procedure

- The Landsat Processing System performs ACCA on every image prior to archiving
- Cloud cover scores (percentages) are tabulated and reported on a quarter scene and full scene basis
- Cloud cover scores are recorded in scene metadata records

Purpose

- ACCA scores are available to users for identifying candidate imagery
- Cloud cover scores are referenced daily by the Mission Operations Center to determine image acquisition success or failure (based on long term acquisition plan criteria)



Evaluation Procedure


- 32 daylight WRS locations were generated randomly across space and time
- Browse imagery and ACCA scores were extracted from the archive
- A variety of Adobe Photoshop tools were used to generate binary cloud masks from each of the browse images
- Histograms of the cloud masks yielded the cloud mask percentages
- The cloud mask scores were compared against the ACCA scores and summarized



Cloud Mask Generation

Browse Image

Photoshop Mask





ACCA versus Mask Scores

Of the 32 images examined:

- 16 (50%) were within 5%
- **24 (75%) were within 10%**
- **28 (88%) were within 15%**
- 29 (91%) were within 20%
- 3 images differed by more than 20%


Assuming the mask is truth:

- ACCA over reported in 13 cases
- ACCA under reported in 16 cases
- ACCA and the mask were the same in 3 cases



Path 154, Row 6 - 10/15/99

Northern Siberia



Anomalous Image # 1


ACCA Score: 78%

Mask Score: 99%



Path 55, Row 119 - 12/11/99

Eastern Antarctica



Anomalous Image # 2


ACCA Score: 0%

Mask Score: 56%



Path 122, Row 27 - 12/17/99

Inner Mongolia



Anomalous Image # 3


ACCA Score: 31%

Mask Score: 0%



Path 122, Row 27 - 11/15/99

Inner Mongolia



ACCA Score: 0%

Mask Score: 0%



Score Comparison

Assuming the mask is truth:

- ACCA over reported in 13 cases
- ACCA under reported in 16 cases
- ACCA and the mask were the same in 3 cases

ACCA vs mask scores (30 of 32 images)

Mean difference: 0.067

Standard deviation: 8.39



Conclusions

- ACCA, in most cases, appears to be working as designed.
- Where ACCA failed, snow was clearly involved
- The ACCA algorithm was based on the Landsat 5 pre-launch calibration, thus, results are very encouraging
- Analysis of the 2 failed scenes is underway. Pre-launch tests indicated successful snow-cloud discrimination. A simple parameter change in the CPF may provide the appropriate fix
- Future ACCA assessments will be performed to ensure algorithm stability